



HIGH FREQUENCY TRANSFORMERS


EEL Series





www.eifter.com

[home>>index](#)


According EN61558, EN60590, EN60472, UL506, UL1585, UL5085 · External protection



HORIZONTAL



VERTICAL



MECHANICAL AND ELECTRICAL PARAMETERS

HORIZONTAL	A (Max)	B	C	D	E	F	MAX POWER
EEL16	18.5	28.0	16.5	23.0	4.0	0.6	4W
EEL19	22.0	32.0	16.5	24.2	4.0	0.6	6W
EEL22	28.5	35.0	21.0	27.5	4.0	0.6	10W
EEL25	27.5	34.0	21.0	27.5	4.0	0.6	15W

VERTICAL	A (Max)	B	C	D	E	F	MAX POWER
EEL16	18.5	17.5	32	12.2	4.0	0.6	4W
EEL19	20.5	17.5	33	12	4.0	0.6	6W
EEL22	26.0	18.0	35.0	13.5	4.0	0.6	10W
EEL25	26.0	18.0	35.0	13.5	4.0	0.6	15W

- All measures are in mm.
- Customized Request

FEATURES

- Power range: 4 Wto 50W
- Operating Frequency: 50 to 200KHz
- Power range:4w to 50W
- Magnetic flux leakage small,high power density, suitable for flags desing.
- Operating temperature: -40°C to +105°C
- All parts meet ROHS compliance
- Construction according to regulation IEC EN60950, EN 61558
- Creepage distance according to regulation IEC EN60950, EN 61558, EN 60335
- Non standard transformers on request