





# HIGH FREQUENCY TRANSFORMERS EF Series






[www.efiter.com](http://www.efiter.com)

[home>>index](#)

According EN61558, EN60590, EN60472, UL506, UL1585, UL5085 · External protection



HORIZONTAL



VERTICAL

## MECHANICAL AND ELECTRICAL PARAMETERS

HORIZONTAL	A	B	C	D	E	F	MAX POWER
EF12,6	14.0	16.0	11,5	10,16	3,5	0,5	15W
EF16	18.0	20.0	14.0	15,24	3,5	0,6	20W
EF20	21,5	21,5	15,8	15,24	3,5	0,6	30W
EF25	27,5	28,5	20.0	20.0	3,5	0,7	45W

VERTICAL	A	B	C	D	E	F	MAX POWER
EF12,6							15W
EF16	17,8	12,6	20,5	8,9	3,5	0,6	20W
EF20	22	13,9	24,5	10,16	3,5	0,6	30W
EF25	27,5	18,9	27.0	12,7	3,5	0,7	45W

- All measures are in mm.
- Customized Request

## FEATURES

- Operating Frequency: 50 to 200KHz
- Power range:15W to 45W
- Magnetic flux leakage small,high power density, suitable for flags desing.
- Operating temperature: -40°C to +105°C
- All parts meet ROHS compliance
- Construction according to regulation IEC EN60950, EN 61558
- Creepage distance according to regulation IEC EN60950, EN 61558, EN 60335
- Non standard transformers on request