




HIGH FREQUENCY TRANSFORMERS ETD Series




www.efiter.com

[home>>index](#)



According EN61558, EN60590, EN60472, UL506, UL1585, UL5085 · External protection



HORIZONTAL



VERTICAL



MECHANICAL AND ELECTRICAL PARAMETERS

HORIZONTAL	A	B	C	D	E	F	MAX POWER
ETD29	36	36	26,5	25,4	4,5	0,8	15W
ETD34	40,5	42,5	34,5	25,4	4,5	0,8	20W
ETD39	42,9	47,6	36,6	30,48	4,5	1	30W
ETD44	49,6	52,2	38,1	35,56	4,5	1	45W
ETD49	54,5	57,2	40,6	40,64	4,5	1	55W

VERTICAL	A	B	C	D	E	F	MAX POWER
ETD29	35	23,8	41,5	20,32	4,5	0,8	15W
ETD34	39,6	27	44	22,86	4,5	0,8	20W

- All measures are in mm.
- Customized Request

FEATURES

- Operating Frequency: 50 to 200KHz
- Power range:15W to 55W
- Magnetic flux leakage small,high power density, suitable for flags desing.
- Operating temperature: -40°C to +105°C
- All parts meet ROHS compliance
- Construction according to regulation IEC EN60950, EN 61558
- Creepage distance according to regulation IEC EN60950, EN 61558, EN 60335
- Non standard transformers on request