




COMMON MODE POWER LINE CHOKE

HR1900/ HR 1901/ HR 1902 SERIES



www.efiter.com

home>>index

According DIN EN 60938-2(VDE 0565-2-1):2008-02; EN 60938-2:1999+A1:2007

FEATURES

- Rated voltage 250VAC
- Rated inductance 0,2mH to 47mH
- Rated current 0,3A a 6A
- Turns ratio:N1:N2=1:1(+/- 2%)
- Hi-Pot_Pri_Sec 1500vac/5mA/2sec
- Operating temperature: -40°C to +105°C
- All parts meet ROHS compliance

ELECTRICAL CHARACTERISTICS

PART Number	Inductance (mH) +50/-30%	Leakage Inductance (uH)typ	DC Resistance (mΩ)typ	Rated current (mA)
HR 190X 000	47	500	2200	300
HR 190X 001	39	450	2000	400
HR 190X 002	27	290	1400	500
HR 190X 003	18	250	1100	500
HR 190X 004	15	170	700	600
HR 190X 005	10	110	550	700
HR 190X 006	6.8	80	280	1200
HR 190X 007	3.3	37	180	1500
HR 190X 008	1.0	13	80	2000
HR 190X 009	0.6	8	60	2500
HR 190X 010	0.4	6	35	3600
HR 190X 011	0.3	4	30	4000
HR 190X 012	0.2	2.5	15	6000

TECHNICAL INFORMATION

