



# COMMON MODE POWER LINE CHOKE

## HR1906, HR 1907, HR 1908 SERIES



www.efiter.com

home>>index

According DIN EN 60938-2(VDE 0565-2-1):2008-02; EN 60938-2:1999+A1:2007

### FEATURES

- Rated voltage 250VAC
- Rated current 0,5A a 8A
- Rated inductance 0,45mH to 56mH
- Turns ratio:N1:N2=1:1(+/- 2%)
- Hi-Pot\_Pri\_Sec 1500vac/5mA/2sec
- Operating temperature: -40°C to +105°C
- All parts meet ROHS compliance

### ELECTRICAL CHARACTERISTICS

PART Number	Inductance (mH) +50/-30%	Leakage Inductance (uH)typ	DC Resistance (mΩ)typ	Rated current (mA)
HR 190X 000	56	680	1800	500
HR 190X 001	47	580	1450	600
HR 190X 002	39	430	750	1000
HR 190X 003	27	270	440	1400
HR 190X 004	10	130	240	1800
HR 190X 005	5.6	70	160	2000
HR 190X 006	2.7	30	60	4000
HR 190X 007	1.0	12	22	6000
HR 190X 008	0.45	5	11	8000

### TECHNICAL INFORMATION

