




"SV" TRANSFORMER


SV E175 to E196





www.efiter.com
home>>index

ENCAPSULATED TRANSFORMERS

According EN61558, EN60590, EN60472, UL506, UL1585, UL5085 · Short circuit proof



UNITATS: mm.
TOLERÀNCIA GENERAL
ISO 2768 - c



DIM(mm)	A	B	C	D	POWER
E7522/40°C	105	66,2	41,9	52,6	35VA 40°C/B
E7522/70°C	105	66,2	41,9	52,6	30VA 70°C/B
E7527/40°C	105	66,2	46,9	57,6	35VA 40°C/B
E7527/70°C	105	66,2	46,9	57,6	30VA 70°C/B
E7533/40°C	105	66,2	53,1	63,8	35VA 40°C/B
E7533/70°C	105	66,2	53,1	63,8	30VA 70°C/B
E7542/40°C	105	66,2	62	72,6	35VA 40°C/B
E7542/70°C	105	66,2	62	72,6	30VA 70°C/B
E7827/40°C	112,5	71,5	48,3	59	50VA 40°C/B
E7827/70°C	112,5	71,5	48,3	59	45VA 70°C/B
E7836/40°C	112,5	71,5	48,3	59	60VA 40°C/B
E7836/70°C	112,5	71,5	48,3	59	55VA 70°C/B
E7840/40°C	112,5	71,5	48,3	59	70VA 40°C/B
E7840/70°C	112,5	71,5	48,3	59	65VA 70°C/B
E8429/40°C	120	74,4	65,4	61,4	75VA 40°C/B
E8429/70°C	120	74,4	65,4	61,4	70VA 70°C/B
E8444/40°C	120	74,4	79,4	75,7	16VA 40°C/B
E8444/70°C	120	74,4	79,4	75,7	13VA 70°C/B
E9635/40°C	133	85	60,5	74,6	130VA 40°C/B
E9635/70°C	133	85	60,5	74,6	125VA 70°C/B
E9645/40°C	133	85	70,5	84,6	160VA 40°C/B
E9645/70°C	133	85	70,5	84,6	155VA 70°C/B
E9660/40°C	133	85	84,7	98,5	200VA 40°C/B
E9660/70°C	133	85	84,7	98,5	195VA 70°C/B

According EN61558, EN60590, EN60472, UL506, UL1585, UL5085 .